

MY24 OUTLANDER DPS 500 T ABS



Granite Gray

ENGINE	500
Type	30 kW (40 hp) / 37 lb-ft, Rotax® ACE (Advanced Combustion Efficiency) 650 cc, single cylinder, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	pDrive primary CVT L / H / N / R / P
Drive Train	Selectable 2WD / 4WD Visco-Lok† ABS (Open differential) with BTC (Brake torque Control)
Driving Assistance	N/A
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
Speed Category	More than 60 km/h

SUSPENSIONS

Front Suspension	Double A-Arm 9.75 in. (24.8 cm) travel
Front Shocks	Twin tube
Rear Suspension	Double A-Arm 10.25 in. (26 cm) travel
Rear Shocks	Twin tube

TIRES & WHEELS

Front & Rear Tires	25 x 8/10 x 12 in. (63.5 x 20.3 / 25.4 x 30.5 cm)
Wheels	12 in. (30.5 cm) cast aluminum

BRAKES

Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm disc brake with hydraulic twin-piston caliper

PACKAGE HIGHLIGHTS

- Tri-Mode Dynamic Power Steering (DPS)
- Anti-Lock Braking System (ABS)
- Full skid plate
- LED headlights with LED signature
- Tow Ball & new flashers

DIMENSIONS & CAPACITIES

Estimated Dry Weight*	767.6 lb (348.2 kg)
L x W x H	86.7 x 47.6 x 56.9 in. (220.2 x 120.9 x 144.6 cm)
Wheelbase	53 in. (134.5 cm)
Ground Clearance	12 in. (30.5 cm)
Seat Height	38 in. (96.7 cm)
Rack Capacity	Front: 120 lb (54.4 kg) / Rear: 240 lb (109 kg)
Storage Capacity	9 gal (34 L)
Towing Capacity	1,830 lb (830 kg) trailer with brake 870 lb (394 kg) without brakes
Fuel Capacity	5.1 gal (19.5 L)

FEATURES

Gauge	4.5 in. digital display
Instrumentation	N/A
Ignition	RF Digitally Encoded Security System (D.E.S.S.™)
Lighting	LED headlights and taillights LED signature
Winch	N/A
T-Category features	Towing hitch with trailer plug, directional indicators, position lamps, mirrors, horn
Seat	Standard
Handlebar	Standard
Protection	Full Skid plate

WARRANTY

Factory Warranty	2-year BRP limited warranty
------------------	-----------------------------



©2024 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, ® and the BRP logo are trademarks of BRP or its affiliates. *Base model dry weight shown. †All trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer. ATVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by the age of 16 and older. Never carry passengers on any ATV not specifically designated for such use. Some models depicted may include optional equipment.



REQUEST A QUOTE



MY24 OUTLANDER DPS 700 T ABS



 Legion Red

ENGINE	700
Type	37 kW (50 hp) / 41 lb-ft, Rotax® ACE (Advanced Combustion Efficiency) 650 cc, single cylinder, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	pDrive primary CVT L/H/N/R/P
Drive Train	Selectable 2WD / 4WD Visco-Lok† ABS (Open differential) with BTC (Brake torque Control)
Driving Assistance	Work / Standard / Sport modes
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
Speed Category	More than 60 km/h

SUSPENSIONS	
Front Suspension	Double A-arm 9.75 in. (24.8 cm) travel
Front Shocks	Twin tube
Rear Suspension	Double A-arm 10.25 in. (26 cm) travel
Rear Shocks	Twin tube

TIRES & WHEELS	
Front & Rear Tires	25 x 8/10 x 12 in. (63.5 x 20.3 / 25.4 x 30.5 cm)
Wheels	12 in. (30.5 cm) cast-aluminum

BRAKES	
Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm disc brake with hydraulic twin-piston caliper

PACKAGE HIGHLIGHTS

- Tri-Mode Dynamic Power Steering (DPS)
- Anti-Lock Braking System (ABS)
- Work / Standard / Sport modes
- Visco-Lok† QE auto-locking front differential
- Full skid plate
- Tow Ball & new flashers

DIMENSIONS & CAPACITIES	
Estimated Dry Weight*	767.6 lb (348.2 kg)
L x W x H	86.7 x 47.6 x 56.9 in. (220.2 x 120.9 x 144.6 cm)
Wheelbase	53 in. (134.5 cm)
Ground Clearance	12 in. (30.5 cm)
Seat Height	38 in. (96.7 cm)
Rack Capacity	Front: 120 lb (54.4 kg) / Rear: 240 lb (109 kg)
Storage Capacity	9 gal (34 L)
Towing Capacity	1,830 lb (830 kg) trailer with brake 870 lb (394 kg) without brakes
Fuel Capacity	5.1 gal (19.5 L)

FEATURES	
Gauge	4.5 in. digital display
Instrumentation	N/A
Ignition	RF Digitally Encoded Security System (D.E.S.S.™)
Lighting	LED headlights and taillights LED signature
Winch	N/A
Seat	Standard
Handlebar	Standard
Protection	Full skid plate

WARRANTY	
Factory Warranty	2-year BRP limited warranty



REQUEST A QUOTE



©2024 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, ® and the BRP logo are trademarks of BRP or its affiliates. *Base model dry weight shown. †All trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer. ATVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by the age of 16 and older. Never carry passengers on any ATV not specifically designated for such use. Some models depicted may include optional equipment.