

# MY24 TRAXTER XU HD9 T ABS



Tundra Green  
 Stone Gray

## ENGINES

Type	48 kW (65 hp) / 59 lb-ft, Rotax® 976 cc, V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	PRO-TORQ CVT with Quick Response System (QRS), high airflow ventilation and Electronic Drive Belt Protection Extra-L / H / N / R / P
Drive Train	Selectable Turf Mode / 2WD / 4WD with Open front differential with ABS system
Driving Assistance	Electronic Hill Descent Control ECO™ / ECO™ Off / Work modes Brake holding mechanism
Power Steering	Dynamic Power Steering (DPS)
Speed Category	More than 60 km/h

## SUSPENSIONS

Front Suspension	Arched double A-arm / 11 in. (27.9 cm) travel
Front Shocks	Twin tube gas charged shocks
Rear Suspension	Arched TTA with external sway bar / 11 in. (27.9 cm) travel
Rear Shocks	Twin tube gas charged shocks

## TIRES / WHEELS

Front Tires / Rear Tires	Maxxis Coronado† 27 x 9 / 11 x 14 in. (68.6 x 22.9 / 27.9 x 35.6 cm)
Wheels	14 in. (35.6 cm) cast-aluminum

## BRAKES

Front	Dual 220 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 220 mm disc brakes with hydraulic single-piston calipers

## HIGHLIGHTS

- Dynamic Power Steering (DPS)
- Anti-Lock Braking System (ABS)
- 14 in. (35.6 cm) cast-aluminum wheels
- 27 in. (68.6 cm) Maxxis Coronado† tires
- 4,500-lb (2,041 kg) winch
- RF Digitally Encoded Security System (D.E.S.S.™)
- Heater-ready

## DIMENSIONS / CAPACITIES

Cage	Profiled cage. ROPS approved
Estimated Dry Weight*	1,572 lb (713 kg)
L x W x H	125.7 x 64 x 80 in. (319.4 x 162.5 x 203.2 cm)
Wheelbase	83 in. (211.5 cm)
Ground Clearance	13 in. (33 cm)
Cargo Box Dimensions	38 x 54.5 x 12 in. (96.5 x 138.4 x 30.5 cm)
Cargo Box Capacity	1,000 lb (454 kg)
Power tilt bed	N/A
Tailgate Load Capacity	250 lb (113.4 kg)
Storage Capacity	Total: 6.5 gal (24.5 L)
Towing Capacity	2,500 lb (1136 kg)
Payload Capacity	1,500 lb (680 kg)
Fuel Capacity	10.6 gal (40 L)
Person Capacity	3

## FEATURES

Gauge	7.6 in. (19.3 cm) wide digital display with keypad
Battery	12-V (30 amp/h)
Magneto	650-W
Instrumentation	DC outlet (10-A)
Lighting	Front lighting output 140 W LED tail lights with halo glow effect
Winch	4,500-lb (2,041 kg) winch with roller fairlead
Seat	VERSA-PRO bench seat with passenger seats flipping up, underside hooks, reinforced seat skin
Steering Wheel	Adjustable tilt steering
Protection	Integrated front steel bumper HMWPE full skid plate Front Fender Extension
Anti-Theft System	RF Digitally Encoded Security System
Hitch Type	2-in hitch receiver with rear hitch, tow ball and trailer connexion
T-Cat Features	Horn, flashers and position lamps, side mirrors, license plate support, hook on front metal bumper

## WARRANTY

Factory warranty	2-year BRP limited warranty
------------------	-----------------------------



REQUEST A QUOTE



©2024 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, ® and the BRP logo are trademarks of BRP or its affiliates. \*Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrive GmbH. ‡All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all SSV drivers take a training course. For safety and training information, see your dealer. SSVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. SSVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any SSV not specifically designated for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.